IVC MobileVision Products MVT-3001

- Customizable mobile surveillance platform
- Solar or engine powered
- Large battery backup
- Operates in extreme environments
- Remotely monitored and controlled
- 24/7 unattended operation
- Wide track trailer for maximum stability
- Multiple camera options











► MVT-3001 Trailer Specifications

| Trailer Dimensions | |
|------------------------|---|
| Width | 1781mm/5' 8" |
| Length | 4040mm/13'2" |
| Height | 3048mm/10' |
| Weight | 1270Kg/2800lbs |
| Camera / Equipment Box | Mounted at top of mast 2 CAT6 & 1.6mm/4 Electric Cables |
| Trailer Details | |
| Axle | A/T single axle |
| Mast Raise/Extension | 24VDC Electric winch |
| Mast height | 25ft Mast |
| Wind Rating Speed | 100kph |
| Lighting Package | USDOT-approved |
| Anti-theft Measures | Locking compartments & wheel locks |
| Battery | |
| Batteries | 6 x 150AH |
| Capacity | 900AH |
| Voltage | DC 12V |
| Material | Colloid |
| Supplied Voltage | 24V |

IVC surveillance trailers are wellsuited for use in a variety of security & monitoring applications.



Remote Construction Monitoring

Emergency Management





Public Safety/Event Management

► MVT-3001 Standard Options

Power plant

- 990 watt solar array
- Combustion engine
- 100 240 VAC
- Storage battery array

Cameras

- 1 5 camera configurations
- 30x HD PTZs with or without integrated illumination
- HD fixed cameras
- Standard and radiometric thermal cameras
- LPR (license plate recognition) cameras

Local audio/visual alarm indicators

Local NVR for video storage and management Wireless connectivity

- 4G LTE cellular w/WiFi
- 2.4GHz. 5GHz radio

2-way audio





Remote Facilities Monitoring



